

LUBRAX COMPSOR DE

High performance synthetic oil for reciprocating air compressors. Available in ISO grade 100. The compatibility between the oil and elastomers, plastics and paints should be checked.

Lubrax Compsor DE is fully formulated industrial lubricant based upon a combination of specially selected synthetic esters, synthetic hydrocarbon and an ash-free additive system.

Lubrax Compsor DE has excellent oxidation resistance, thermal stability and solvency result in improved system cleanliness and increased service life of the lubricant.

Lubrax Compsor DE protects the lubricated parts against wear and corrosion, even with the adverse effects in moist environments.

Lubrax Compsor DE provides good low temperature fluidity performance. The product can be used in a wide temperature range.

Lubrax Compsor DE is recommended for the lubrication of reciprocating machines operating under heavy-duty conditions. Suited for the lubrication of anti-friction bearing assemblies operating under high temperature conditions, such as fans, blowers, process pumps, and enclosed gear drives operating under light load conditions.

Lubrax Compsor DE reduces maintenance costs by preserving and keeping the compressor components cleaner.

TYPICAL ANALYSIS*

ISO GRADE		100
Density at 15°C	(kg/L)	0.962
Flash Point (COC)	(°C)	252
Pour Point	(°C)	-40
Viscosity @ 40°C	(cSt)	95.5
Viscosity @ 100°C	(cSt)	10.1
Viscosity Index	-	83
Phosphorus Content	(%wt)	0.18
Sulphur Content	(%wt)	0.25
Nitrogen Content	(%wt)	0.11

*The above results are typical of those obtained with normal production tolerances, and do not constitute a specification. For further details please contact our technical support service.

January/2011

