

LUBRAX COMPSOR AC

Lubricating oil for air, helium, nitrogen or carbon dioxide compressors. Available in ISO grades 32, 46, 68, 100, 150 and 220.

Lubrax Compsor AC prevents wear and corrosion of the lubricated parts. Its additives assure low oil oxidation, low foaming and resistance to aeration.

Lubrax Compsor AC holds small particles in suspension, thanks to its detergent/dispersant additives, keeping the machines clean.

Lubrax Compsor AC may also be used in systems subject to water contamination, such as hydraulic and circulating systems, paper industries and also in reduction gears, pumps, heating systems, vacuum pumps, particularly in marine equipment.

Lubrax Compsor AC may be used whenever a DIN-51506 VD-L oil is required.

Additives - antirust, antiwear, antifoam, antioxidant, detergent, dispersant, metal deactivator and pour point depressant.

TYPICAL ANALYSIS*

ISO GRADE	32	46	68	100	150	220
Specific Gravity at 20/4°C	0.8769	0.8817	0.8877	0.8896	0.8926	0.8979
Flash Point (COC) (°C)	228	232	246	266	274	284
Pour Point (°C)	-33	-33	-27	-21	-18	-18
Viscosity at 40°C (cSt)	34.2	44.1	64.0	97.1	143.3	210
Viscosity at 100°C (cSt)	5.78	6.78	8.46	11.03	14.38	18.57
Viscosity Index	110	108	102	98	98	98
Total Base Number (mgKOH/g)	3.5	3.5	3.5	3.5	3.5	3.5
Sulfated Ash (% wt)	0.67	0.67	0.67	0.67	0.67	0.67

*The above results are typical of those obtained with normal production tolerances, and do not constitute a specification. For further details please contact our technical support service.

January/2011