

LUBRAX LITHPLUS EP 2

Multipurpose complex lithium soap lubricating grease for industrial and automotive applications. Available in NLGI grade 2.

LUBRAX LITHPLUS EP 2 contains sulfur and phosphorous extreme pressure additives and is lead free.

LUBRAX LITHPLUS EP 2 has a very good performance even in high and low temperatures, oxidation resistance, antiwear, and extreme pressure characteristics, together with an excellent mechanical stability.

LUBRAX LITHPLUS EP 2 is recommended for lubrication of parts subject to high loads and shock loads. It can be used in roller or slide bearings, gears and coupling found in steel mill rollers, paper machines, press crushers and cranes, and couplings and wheel centers in automotive applications.

LUBRAX LITHPLUS EP 2 can be used continuously under high temperatures (until 250°C) or low temperatures (until -20°C). It has an excellent water washout resistance and rust protection, and can be applied by pistol or centralized systems.

Additives - antioxidant, anti-rust and extreme pressure agent.

TYPICAL ANALYSIS *

NLGI GRADE		2
Worked Penetration, 60x	(0.01 mm)	279
Worked Penetration, 10.000x	(0.01 mm)	284
Drop Point	(°C)	>260
Timken OK Load	(lb)	45
Four Ball, weld load	(kg)	250
Base Oil Characteristics		
Viscosity at 40°C	(cSt)	151.7
Viscosity at 100°C	(cSt)	14.91

* The above results are typical of those obtained with normal production tolerances, and do not constitute a specification.

January/2011

