

LUBRAX COMPSOR GAS

High performance synthetic lubricant for gas compressors.

Lubrax Compсор GAS is a 100% synthetic lubricating oil, PAG (polyalkylene glycol) based specifically formulated for the lubrication of gas compressors in marine and industrial service.

Lubrax Compсор GAS provides excellent wear protection, high thermal stability, minimal gas solubility and reduced foaming. It's recommended for use in Burckhardt Compression AG's K-type gas compressors.

Lubrax Compсор GAS should not be mixed with mineral oil and other synthetic type fluids.

Lubrax Compсор GAS is recommended for the use in enclosed type compressors operating on liquefied natural gases (methane, ethane) liquefied petroleum gases (propane, butane), hydrocarbon chemical gases (ethylene, propylene and butylene) and other chemical gases such as ammonia, VCM and butadiene. Under these conditions the gas is soluble in the mineral oil and the viscosity loss could affects lubrication performance

TYPICAL ANALYSIS*

GRADE**	180
Specific Gravity @ 20/4°C	1.0500
Flash Point (COC) (°C)	260
Pour Point (°C)	-30
Viscosity @ 40°C (cSt)	185
Viscosity @ 100°C (cSt)	35.0
Viscosity Index	238

*The above results are typical of those obtained with normal production tolerances, and do not constitute a specification.

**It's not ISO grade.

For further details please contact our technical support service.

January/2011

