

# LUBRAX CALCIUM ECO 2

Biodegradable calcium complex based lubricating grease. Available in NLGI grade 2.

**LUBRAX CALCIUM ECO 2** is a special lubricating grease, formulated with a calcium complex soap, showing environmental benefits and providing excellent protection against corrosion, wear and water contamination, even in hostile conditions.

**LUBRAX CALCIUM ECO 2** is suitable for use across a wide temperature range, up to 120°C, with a maximum temperature peak of 140°C. The good pumpability allows the use of pressurized lubrication systems during the lubrication. Its special thickener grants excellent surface adherence and water spray-off resistance, keeping the equipment protected longer.

**LUBRAX CALCIUM ECO 2** is recommended for marine, offshore and industrial applications where a high-performance biodegradable grease is required. It is particularly recommended for the lubrication and protection of wire ropes in shipyards, ports, ships and oil & gas production and exploration platforms in sensitive marine environments.

Additives – antioxidant and corrosion inhibitor.

## TYPICAL ANALYSIS \*

NLGI GRADE		2
Worked Penetration 60x	(0,1 mm)	280
Dropping Point	(°C)	> 250
Salt Spray Test (ASTM B-117)		Pass
Rust Test (ASTM D-1743)	-	Pass
Base Stock		
Viscosity @ 40°C	(cSt)	32,0
Viscosity @ 100°C	(cSt)	7,71

\* The above results are typical of those obtained with normal production tolerances, and do not constitute a specification.

February/2012

