

LUBRAX COMPSOR RF

Lubricating oil for refrigeration and air conditioning compressors used in marine and industrial equipment. Available in ISO grades 32, 46, 68, 100, 115** and 150.

Lubrax Compсор RF is formulated with naphthenic base stocks which allow its use in open refrigeration systems, and it is moisture-free.

Lubrax Compсор RF is compatible with the majority of refrigeration gases, like ammonia, carbon dioxide, methyl chloride, freons, which show low solubility in oil.

Lubrax Compсор RF can also be used whenever required a naphthenic oil without special additives.

TYPICAL ANALYSIS*

ISO GRADE	32	46	68	100	115**	150
Specific Gravity at 20/4°C	0.9035	0.9050	0.9079	0.9106	0.9074	0.9170
Flash Point (COC) (°C)	180	184	194	212	216	220
Pour Point (°C)	-39	-36	-33	-27	-27	-21
Viscosity at 40°C (cSt)	30.0	43.0	64.2	108.2	116.0	144.0
Viscosity Index	3	16	17	12	7	8
Neutralization Number (mgKOH/g)	0.01	0.01	0.01	0.01	0.01	0.01
Dielectric Strength (KV)	40	38	41	37	42	31
Copper Strip Corrosion. 3h, 100°C	1b	1b	1b	1b	1b	1b

*The above results are typical of those obtained with normal production tolerances, and do not constitute a specification.

**It's not ISO grade.

For further details please contact our technical support service.

January/2011

