

LUBRAX BETUMEN FLD ...

Asphalt based lubricating grease, diluted with volatile non-flammable solvent, for heavy equipment lubrication. Available in grades 250 e 500.

LUBRAX BETUMEN FLD ... has properties of adhesion to metal surfaces and resistance to water washout and after solvent evaporation it forms a flexible and adherent film, which allows its use even in equipment exposed to the atmosphere.

LUBRAX BETUMEN FLD ... is recommended for the lubrication of low speed open gears, chains, wire ropes and heavy machinery in general, either agricultural, industrial, building, earthwork, transportation or mining. It may be applied manually, as with brushes, by immersion, grease pistols and hand oilers as well as by means of centralized systems.

LUBRAX BETUMEN FLD 250 is approved by KRUPP POLYSIUS and VILLARES for use in exposed chains and ropes.

TYPICAL ANALYSIS *

GRADES		250	500
Specific Gravity at 20/4 °C		1,075	1,076
Flash Point (COC) (without solvent)	(°C)	300	310
Viscosity at 100°C (without solvent)	(cSt)	398,5	911,6
Viscosity at 50°C (with solvent)	(cSt)	242,6	376,8
Non-volatile Residue	(% wt.)	72	72
Timken OK Load (Asphalt Base)	(lb)	>25	>25

* The above results are typical of those obtained with normal production tolerances, and do not constitute a specification.

January/2011