

LUBRAX COMPSOR PAO

High performance synthetic oils for air compressors. Available in ISO grades 32, 46 e 68.

Lubrax Compсор PAO is a range of 100% synthetic lubricating oils, PAO (polyalphaolefin) based. It's specially formulated to assure excellent oxidation resistance, good demulsibility and high thermal stability.

Lubrax Compсор PAO protects the lubricated parts against wear and corrosion, even with the adverse effects in moist environments. Its formulation provides good low temperature fluidity performance. The product can be used in a wide temperature range.

Lubrax Compсор PAO is recommended for the lubrication of rotary and centrifugal air compressors operating under severe conditions in marine and industrial applications.

Lubrax Compсор PAO reduces maintenance costs by preserving and keeping the compressor components cleaner. The drain intervals can be up to 8 times longer if compared to mineral oils

TYPICAL ANALYSIS*

ISO GRADE	32	46	68
Specific Gravity @ 20/4°C	0.8454	0.8406	0.8600
Flash Point (COC) (°C)	254	276	260
Pour Point (°C)	-57	-57	-48
Viscosity @ 40°C (cSt)	29.9	42.3	69.5
Viscosity @ 100°C (cSt)	5.90	7.30	12.4
Viscosity Index	146	137	180

*The above results are typical of those obtained with normal production tolerances, and do not constitute a specification. For further details please contact our technical support service.

January/2011